

PROCAT™ 6000MX



MODEL NUMBER	9996005	9996006
ENGINE		
Model	Kaw FX850V	Kaw FX850V
Displacement (cc)	852	852
Fuel Capacity (gal)	15	15
Air Filter	Canister Air Filter	
ELECTRICAL		
Charging System (amp)	15	15
Clutch (ft lb)	225	225
DECK		
Mower Deck	AirFX™ Cutting System	
Leading Edge	Adjustable, Front Lip Standard	
Width (in)	61	61
Adjustable Anti-Scalp Rollers	6	6
Cutting Height (in)	1–5.5	1–5.5
Blade Tip Speed	18500 fpm @ 3550 Engine rpm	18500 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer	
FRAME		
Front & Rear	Welded 0.25 in, 7-gauge Steel; 1.5 x 2.5 in Steel Tubing	
Machine Length (in)	83	83
Machine Weight—Wet (lb)	1464	1517
TRANSMISSION		
Type	HG ZT-4400 Hydrostatic Transaxles	HG Pumps with HG Wheel Motors
Pump Displacement (cc)	12	12
Oil Capacity (qt)	4.5 each	9
Forward Speed (mph)	0–12	0–11
Reverse Speed (mph)	0–4	0–4
WHEELS		
Drive Wheel Size	24 x 12.0–12, 6-Spoke	24 x 12.0–12, 6-Spoke
Front Caster Wheel Size	13 x 6.5–6	13 x 6.5–6
Caster Arm Attachment	Bolt-On	Bolt-On
SEAT		
Description	High-Back, Full-Mechanical Suspension Seat	
Fore-Aft Adjustment	Seat Slide Lever	
WARRANTY		
	6-year / 2,750 hour MOW WITH CONFIDENCE™ limited warranty	

Parts & Accessories: Mulching Baffle Kit – Eliminator Blades, Eco Plate, Grass Catcher – Poly-Dump—3.75 or 5.0 bushel, BOSS-Vac™ Pro 12-bushel, BOSS-Vac™ 8-bushel, No-Flat Caster Wheel Options, 61-inch Wide Track Kit, Magnetic Light Kit—12V, Striping Kit (48", 52", 61"), Light Kit—Footplate, Operator-Controlled Discharge Chute



FIERCELY INDEPENDENT.

BOBCATTURF.COM